arXiv:1107.0217v3 [cond-mat.soft] 2 Jan 2012

Static and dynamic response of a fluid-fluid interface to electric point and line charge

Simen Å. Ellingsen[1], **Iver Brevik**[1]

[1]Department of Energy and Process Engineering, Norwegian University of Science and Technology, N-7491 Trondheim, Norway

E-mail: simen.a.ellingsen@ntnu.no, iver.h.brevik@ntnu.no

Abstract. We consider the behaviour of a dielectric fluid-fluid interface in the presence of a strong electric field from a point charge and line charge, respectively, both statically and, in the latter case, dynamically. The fluid surface is elevated above its undisturbed level until balance is reached between the electromagnetic lifting force, gravity and surface tension. We derive ordinary differential equations for the shape of the fluid-fluid interface which are solved numerically with standard means, demonstrating how the elevation depends on field strength and surface tension coefficient. In the dynamic case of a moving line charge, the surface of an inviscid liquid-liquid interface is left to oscillate behind the moving charge after it has been lifted against the force of gravity. We show how the wavelength of the oscillations depends on the relative strength of the forces of gravity and inertia, whereas the amplitude of the oscillations is a nontrivial function of the velocity at which the line charge moves.

PACS numbers: 01.40.Ha, 47.65.-d, 41.20.-q, 47.85.Dh

1. Introduction

Electromagnetic manipulation of dielectric soft matter surfaces has emerged to be a topic of considerable interest in later years, both from fundamental and applied points of view. The integration of photonics and microfluidics, *optofluidics*, is a new analytic field - cf., for instance, the reviews [1–3].

One of the first examples of this kind was the classic experiment of Ashkin and Dziedzic [4] on the elevation of a water surface when illuminated vertically from above by a pulsed laser. The force per unit area acting on a dielectric boundary in the presence of an electric field is

$$\mathbf{P}_E = -\frac{\varepsilon_0}{2} E^2 \nabla \varepsilon, \tag{1}$$

The surface elevation of the surface was found to be small, of the order of 1 μm, due to the strong surface tension between air and water [4]. Another noteworthy example on the interaction between light and matter is the experiment of Zhang and Chang [5], showing how the surface of a micrometer water droplet when illuminated by a laser becomes distorted, especially at the rear end because of the lens effect of the sphere. A newer series of experiments is provided by the Bordeaux group [6–8], working with a two-fluid system of surfactant-coated nanodroplets in oil microemulsions near the critical point. The surface tension σ can then be reduced to less than a millionth of

the usual air-water tension, and the surface displacements can accordingly be very large, almost 100 μm. The classical electromagnetic theory of this sort of experiments is given in several papers; cf., e.g., [9] and the review article [10].

The above remarks are related to optical manipulation of liquid surfaces. A close sibling of optofluidics is to make use of *electrostatic fields* instead of optical fields. This field of research, often termed electrohydrodynamics, is not new — cf., for instance, Taylor's seminal 1969 paper [11] — yet in view of the considerable attention given to the optical techniques it is still of interest, not least pedagogically, to understand the electrostatic case. Naturally, the electric force density acting in a boundary layer is basically the same as above, viz. Eq. (1). Since an optical period is much shorter than the mechanical response time of a fluid, optofluidic theory works with time-averaged fields (over an optical period), and similarities are many. But there are obvious differences also. For one thing, the permittivity of a dielectric fluid is usually strongly frequency dependent, and is often much higher in the static case than in the high-frequency optical case.

Formation of liquid columns and extraction of jets by electric fields were studied in seminal experiments of Raco [12] and Taylor [11], and have been a source of investigation at intervals since then. Electrically supported liquid columns have been subjected to stability investigations both experimentally and theoretically [13–16], and the formation of such columns rising against the gravitational force have been shown experimentally [17, 18].

The experiment of Raco [12], in particular, is extreme in that it is very nonlinear and moreover is influenced by the finite conductivity of the liquid. In order to describe such an experiment, a heavy computational machinery is likely to be necessary. However, a useful insight into the fluid-field interaction may be obtained also by analytical methods, on the basis of quite simple models. Our intention is just to describe the fluid interface response with respect to a strong electric field by taking an external point charge Q, or a charged line with charge λ per unit length, to be the source. This simple model has a high degree of flexibility and its analysis is physically transparent as well as mathematically tractable. To some extent, such a theory is related to that given by de Gennes [19] on the pushing of a micro droplet using a laser beam.

We will assume in the following that the typical height h of the surface elevation is much smaller than the distance L between the charge and the undisturbed surface. The reason is that, while the equation giving the fluid deformation in a given electric field is simple to derive, the complementary problem of how the electric field from a point charge is altered by the presence of an arbitrarily shaped dielectric surface is a more difficult problem best solved within computational physics. As is so often the case, however, the problem is analytically tractable when restricted to leading order in the small quantity h/L, which allows calculation of the field at an arbitrary point by method of image charges as if the surface were at rest. Inspection of the governing equations which we derive in the following sections is enough to see that including corrections to the electric fields due to the surface perturbations provides a higher order correction. For consistency we must also linearize the mechanical equations of motion for the surface. The problem is nevertheless nontrivial and physically interesting, and illuminates key features in the theory of electric liquid surface manipulation.

Note finally that it is safe to ignore non-linear dielectric response due to the quadratic electro-optic effect in the following. C.f. e.g. discussion on p. 147 of Ref. [20].

2. Surface elevation arising from a point charge



Figure 1. The geometry considered in section 2.

Consider the setup sketched in Fig. 1: a point charge Q is situated a distance L above the undisturbed liquid surface (the xy plane). In cylindrical coordinates, the position of Q is $r = 0, z = L$. The permittivity in the upper region is ε_1, and in the lower region ε_2. We assume that $\varepsilon_2 > \varepsilon_1$ so that the surface force acts upwards. Now introduce the image charge

$$Q' = -\frac{\varepsilon_2 - \varepsilon_1}{\varepsilon_2 + \varepsilon_1} Q, \tag{2}$$

situated at $r = 0, z = -L$. The potential $\phi_1(r, z)$ at an arbitrary field point P in the upper region is that of the charge Q plus the fictitious charge Q' in a uniform medium of permittivity ε_1 [21],

$$\phi_1 = \frac{1}{4\pi\varepsilon_0} \left(\frac{Q}{\varepsilon_1 R} + \frac{Q'}{\varepsilon_1 R'} \right), \tag{3}$$

where R and R' are the distances QP and Q'P,

$$R = \sqrt{r^2 + (L - z)^2}, \quad R' = \sqrt{r^2 + (L + z)^2}. \tag{4}$$

Furthermore, if Q'' is the image

$$Q'' = \frac{2\varepsilon_2}{\varepsilon_2 + \varepsilon_1} Q, \tag{5}$$

situated at the same position as Q, the potential ϕ_2 in the lower region is that of Q'' in a uniform medium of permittivity ε_2,

$$\phi_2 = \frac{1}{4\pi\varepsilon_0} \frac{Q''}{\varepsilon_2 R}. \tag{6}$$

These expressions satisfy the boundary conditions at $z = 0$, namely that ϕ as well as of $\varepsilon \partial\phi/\partial z$ are continuous.

The radial component $E_{1r} = -\partial\phi_1/\partial r$ and the vertical component $E_{1z} = -\partial\phi_1/\partial z$ of the field in the upper region are

$$E_{1r} = \frac{1}{4\pi\varepsilon_0\varepsilon_1} \left(\frac{Qr}{R^3} + \frac{Q'r}{R'^3} \right), \tag{7}$$

$$E_{1z} = \frac{1}{4\pi\varepsilon_0\varepsilon_1} \left(-Q\frac{L - z}{R^3} + Q'\frac{L + z}{R'^3} \right), \tag{8}$$

which gives for the square $E_1^2 = E_{1r}^2 + E_{1z}^2$ at an arbitrary position r, z the expression

$$E_1^2 = \frac{1}{(4\pi\varepsilon_0\varepsilon_1)^2}\left[\frac{Q^2}{R^4} + \frac{Q'^2}{R'^4} - \frac{2QQ'}{R^3R'^3}(L^2 - r^2 - z^2)\right]. \tag{9}$$

Consider now the elevated surface, $h = h(r)$. The electric pressure acting on it is [20]

$$\begin{aligned}\mathbf{P}_E &= \frac{1}{2}\varepsilon_0(\varepsilon_2 - \varepsilon_1)\left[\frac{\varepsilon_2}{\varepsilon_2}E_{1n}^2 + E_{1t}^2\right]\mathbf{n} \\ &= \frac{1}{2}\varepsilon_0(\varepsilon_2 - \varepsilon_1)\left[\frac{\varepsilon_1}{\varepsilon_2}E_1^2 + \left(1 - \frac{\varepsilon_1}{\varepsilon_2}\right)E_{1t}^2\right]\mathbf{n},\end{aligned} \tag{10}$$

where the normal field $\mathbf{E}_{1n}$ and the tangential field $\mathbf{E}_{1t}$ are evaluated on the outer surface, $z = h^+$, $\mathbf{n}$ being the outward normal vector

$$\mathbf{n} = \frac{-h'\hat{\mathbf{r}} + \hat{\mathbf{z}}}{\sqrt{1+h'^2}}; \quad \mathbf{t} = \frac{\hat{\mathbf{r}} + h'\hat{\mathbf{z}}}{\sqrt{1+h'^2}}. \tag{11}$$

Here $\mathbf{t}$ is a tangential unit vector and $h' = h'(r)$ is the slope of the surface. Thus

$$E_{1t} = \frac{1}{\sqrt{1+h'^2}}(E_{1r} + E_{1z}h'), \tag{12}$$

which is easily calculable from Eqs. (7) and (8) inserting $z = h$.

For computational purposes it is convenient to introduce here a reference field strength E_0, equal to the field due to Q only, at the origin $r = 0, z = 0$,

$$E_0 = \frac{1}{4\pi\varepsilon_0\varepsilon_1}\frac{Q}{L^2}. \tag{13}$$

We can then write, at position $z = h^+$,

$$E_1^2 = E_0^2\left[\frac{1}{(R/L)^4} + \frac{(Q'/Q)^2}{(R'/L)^4} + \frac{2Q'/Q}{(R/L)^3(R'/L)^3}\left(\frac{r^2+h^2}{L^2} - 1\right)\right], \tag{14}$$

$$E_{1t}^2 = \frac{E_0^2}{1+h'^2}\left[\frac{(r/L) - (1-h/L)h'}{(R/L)^3} + \frac{Q'}{Q}\frac{(r/L) + (1+h/L)h'}{(R'/L)^3}\right]^2 \tag{15}$$

(observe that $E_{1n}^2 = E_1^2 - E_{1t}^2$).

For numerical purposes we use the dimensionless quantities

$$\tilde{h} = \frac{h}{L}, \quad \tilde{r} = \frac{r}{L}, \quad \tilde{R} = \frac{R}{L}; \quad \tilde{R}' = \frac{R'}{L}; \quad \tilde{Q} = \frac{Q'}{Q} = -\frac{\varepsilon_2 - \varepsilon_1}{\varepsilon_2 + \varepsilon_1}. \tag{16}$$

Noting $\tilde{h}' = \mathrm{d}\tilde{h}/\mathrm{d}\tilde{r} = h'$ we may write to leading order in h, h'

$$E_1^2 = \frac{E_0^2}{(\tilde{r}^2+1)^2}\left(1 + \tilde{Q}^2 + 2\tilde{Q}\frac{\tilde{r}^2-1}{\tilde{r}^2+1}\right) + \frac{4(1-\tilde{Q})}{(\tilde{r}^2+1)^3}\tilde{h} + ... \tag{17}$$

$$E_{1t}^2 = \frac{E_0^2}{(\tilde{r}^2+1)^3}\left[\tilde{r}^2(1+\tilde{Q})^2 + 2\tilde{r}(1-\tilde{Q}^2)\left(\frac{3\tilde{r}}{\tilde{r}^2+1}\tilde{h} - \tilde{h}'\right)\right] + ... \tag{18}$$

plus corrections of order $\tilde{h}^2, \tilde{h}\tilde{h}'$.

The excess pressure force due to surface-tension is related to the two radii of curvature R_1 and R_2 at a given point by [22]

$$\mathbf{P}_{\text{s.t.}} = p_{\text{s.t.}}\mathbf{n} = \sigma\left(\frac{1}{R_1} + \frac{1}{R_2}\right)\mathbf{n}. \tag{19}$$

We use the sign convention of [22] that the curvature is positive when the surface is concave upwards, which implies that near the maximum of the elevation, the radii are

negative, and the surface tension force points downwards. With a bit of differential geometry this may be written in terms of h and its derivatives as [23]

$$p_{\text{s.t.}} = \frac{\sigma}{r}\frac{d}{dr}\frac{rh'}{\sqrt{1+h'^2}} = \frac{\sigma}{r}(h' + rh'') + ... \tag{20}$$

where σ is the surface-pressure coefficient. The force of gravity is accounted for by noting that a surface elevated by a distance h has a hydrostatic pressure which is lower than that at the unperturbed surface by a difference

$$\Delta p_{\text{hydrostat.}} = -(\rho_2 - \rho_1)gh \tag{21}$$

giving a negative upward (i.e., downward) surface force. Now note that all surface forces are directed normally to the surface. The balance equation is therefore scalar and the stationary situation is found when the net surface force density is zero. Altogether, the governing equation for the surface elevation takes the form

$$(\rho_2 - \rho_1)gh - p_{\text{s.t.}} = \frac{1}{2}\varepsilon_0(\varepsilon_2 - \varepsilon_1)\left[\frac{\varepsilon_1}{\varepsilon_2}E_1^2 + \left(1 - \frac{\varepsilon_1}{\varepsilon_2}\right)E_{1t}^2\right]. \tag{22}$$

As the density ρ_2 of the lower liquid is larger than the density ρ_1 of the upper one, both terms on the left hand side of this equation are positive near $\tilde{r} = 0$, thus both adding to the hydrostatic pressure at the level $z = 0$. This is counterbalanced by the field pressure on the right hand side, acting upwards.

The boundary conditions to equation (24) are

$$\tilde{h}(\infty) = \tilde{h}'(0) = 0. \tag{23}$$

2.1. Numerical and large-r asymptotic solutions

Explicitly, thus, the dimensionless surface elevation $\tilde{h}$ is given as the solution to the second order differential equation

$$\tilde{h}'' + [\tilde{r}^{-1} + Af_1(\tilde{r})]\tilde{h}' + [Af_0(\tilde{r}) - G]\tilde{h} + As(\tilde{r}) = 0 \tag{24}$$

where

$$f_1(\tilde{r}) = -\frac{2\tilde{r}(1-\bar{\varepsilon})(1-\tilde{Q}^2)}{(\tilde{r}^2+1)^3}, \tag{25}$$

$$f_0(\tilde{r}) = \frac{6\tilde{r}^2(1-\bar{\varepsilon})(1-\tilde{Q}^2)}{(\tilde{r}^2+1)^4} + \frac{4\bar{\varepsilon}A(1-\tilde{Q})}{(\tilde{r}^2+1)^3}, \tag{26}$$

$$s(\tilde{r}) = \frac{(1+\tilde{Q})^2\tilde{r}^2 + \bar{\varepsilon}(1-\tilde{Q})^2}{(\tilde{r}^2+1)^3}. \tag{27}$$

and dimensionless parameters

$$A = \frac{\varepsilon_0(\varepsilon_2 - \varepsilon_1)E_0^2 L}{2\sigma}; \quad G = \frac{L^2}{l_c^2}; \quad \bar{\varepsilon} = \frac{\varepsilon_1}{\varepsilon_2}. \tag{28}$$

As is typical for problems involving deformation of liquid surfaces, we may introduce the capillary length

$$l_c = \sqrt{\frac{\sigma}{(\rho_2 - \rho_1)g}}. \tag{29}$$

The quantity A is a relative measure of the influence of the electromagnetic force compared to that from surface tension. G, similarly, is a measure of the force of gravity relative to the surface tension force. In macroscopic geometries surface tension can



Figure 2. Surface elevation for different point charge field strengths (bottom to top) $E_0 = 5 \cdot 10^5$V/m to $1.1 \cdot 10^6$V/m in steps of 10^5V/m. This means Q ranges from 5.6 to 12.2 nC. Parameters are $L = 1$cm, $\varepsilon_1 = 1, \varepsilon_2 = 15, (\rho_2 - \rho_1)g = 9790\text{N/m}^3$. The inset figure is to illustrate the geometry and is not to scale.

often play a very minor role, so both A and G may take values much greater than unity. For a water-air interface, $l_c \approx 2.8$mm [22].

We now turn to the behaviour of $h(r)$ for large r. Letting $\tilde{r} \to \infty$ we have

$$\frac{1}{\tilde{r}} + Af_1 \sim \frac{1}{\tilde{r}}, \quad Af_0 - G \sim -G, \quad As \sim \frac{A(1+\tilde{Q})^2}{\tilde{r}^4}, \tag{30}$$

so if we assume $\tilde{h}$ falls off as a power of $\tilde{r}$, $\tilde{h} \propto \tilde{r}^{-\mu}$, then $f_1\tilde{h}' \propto \tilde{h}'' \propto \tilde{r}^{-\mu-2} \ll f_0\tilde{h}$, so these terms can be neglected in Eq. (24). The asymptotic solution is then trivially found as

$$\tilde{h}(\tilde{r}) \sim \frac{A(1+\tilde{Q})^2}{G\tilde{r}^4} = \frac{\varepsilon_0\varepsilon_1 E_0^2}{g(\rho_2-\rho_1)L}\frac{\varepsilon_2-\varepsilon_1}{\varepsilon_2+\varepsilon_1}\frac{1}{\tilde{r}^4}, \quad \tilde{r} \to \infty. \tag{31}$$

The asymptotic solution is independent of σ as one would expect in an area where the elevation varies slowly with $\tilde{r}$. It is determined by the ratio A/G which is the relative influence of electromagnetic forces and gravity, which is also physically obvious. For numerical purposes it is more useful to use this asymptotic expansion as a boundary condition than $h(\infty) = 0$, since the latter requires needlessly large values of $\tilde{r}$ be used.

The numerical solution of equation (24) with boundary conditions (23) is readily found, and shown in figure 2. We use straightforward Runge-Kutta integration with a shooting loop to find the value of $h(0)$ so that the asymptotic value (31) is met at some large value of r/L.

3. Surface elevation arising from a line charge

Consider now the analogous situation where an infinite charged straight line lies parallel to the undisturbed surface (the xy plane). The line is parallel to the y axis, and intersects the zx plane in the point $x = 0, z = L$. We let now λ denote the charge

per unit length. The images λ' and λ'' are related to λ exactly as Q' and Q'' were to Q in the previous section, by expressions (2) and (5). The potentials are [21]

$$\phi_1 = -\frac{\lambda}{2\pi\varepsilon_0\varepsilon_1}\ln R - \frac{\lambda'}{2\pi\varepsilon_0\varepsilon_1}\ln R', \tag{32}$$

$$\phi_2 = -\frac{\lambda'}{2\pi\varepsilon_0\varepsilon_2}\ln R, \tag{33}$$

where now R and R' are the distances in the xz plane,

$$R = \sqrt{x^2+(L-z)^2}, \quad R' = \sqrt{x^2+(L+z)^2}. \tag{34}$$

We let henceforth $\eta = \eta(x)$ denote the surface elevation. The electric pressure $\mathbf{P}_E$ is given by the same formula (10) as before, where now $\mathbf{E}_{1t}$ is the tangential component of $\mathbf{E}_1$ at the upper surface in the zx plane. An analogous calculation to the one above gives for the desired field quantities, at $z = \eta^+$,

$$E_1^2 = E_0^2\left[\frac{1}{(R/L)^2} + \frac{\lambda'^2}{\lambda^2}\frac{1}{(R'/L)^2} + \frac{2\lambda'/\lambda}{(R/L)^2(R'/L)^2}\left(\frac{x^2+\eta^2}{L^2}-1\right)\right], \tag{35}$$

$$E_{1t}^2 = \frac{E_0^2}{(1+\eta'^2)}\left[\frac{(x/L)-(1-\eta/L)\eta'}{(R/L)^2} + \frac{\lambda'}{\lambda}\frac{(x/L)+(1+\eta/L)\eta'}{(R'/L)^2}\right]^2, \tag{36}$$

where $\eta' \equiv d\eta/dx$ and we have introduced the reference field strength

$$E_0 = \frac{1}{2\pi\varepsilon_0\varepsilon_1}\frac{\lambda}{L}, \tag{37}$$

in analogy to Eq. (13).

The surface-tension pressure is now [22]

$$\mathbf{P}_{\text{s.t.}} = p_{\text{s.t.}}\mathbf{n} = \sigma\frac{\eta''}{(1+\eta'^2)^{3/2}}\,\mathbf{n} \sim (\sigma\eta'' + ...)\mathbf{n}, \tag{38}$$

thus a simpler expression than the previous expression (20). The governing equation thus becomes very similar to the one we found for the point charge

$$(\rho_2-\rho_1)g\eta - p_{\text{s.t.}} = \frac{1}{2}\varepsilon_0(\varepsilon_2-\varepsilon_1)\left[\frac{\varepsilon_1}{\varepsilon_2}E_1^2 + \left(1-\frac{\varepsilon_1}{\varepsilon_2}\right)E_{1t}^2\right], \tag{39}$$

with Eqs. (35) and (36) to be inserted on the right hand side. Boundary conditions are as before,

$$\tilde{\eta}(\infty) = \tilde{\eta}'(0) = 0. \tag{40}$$

3.1. Numerical and asymptotic solution

For numerical purposes we again introduce the non-dimensional quantities (16) and (28). After linearising equation (39) it now reads

$$\tilde{\eta}'' + Af_1(x)\tilde{\eta}' + [Af_0(x) - G]\tilde{\eta} + As(x) = 0 \tag{41}$$

with $\tilde{\eta} = \eta/L$, $\tilde{x} = x/L$ and

$$f_1(\tilde{x}) = -\frac{2(1-\bar{\varepsilon})(1-\tilde{\lambda}^2)\tilde{x}}{(\tilde{x}^2+1)^2}; \tag{42}$$

$$f_0(\tilde{x}) = \frac{2(1-\tilde{\lambda}^2)(2\tilde{x}^2+\bar{\varepsilon}-\bar{\varepsilon}\tilde{x}^2)}{(\tilde{x}^2+1)^3}; \tag{43}$$

$$s(\tilde{x}) = \frac{(1+\tilde{\lambda})^2\tilde{x}^2 + \bar{\varepsilon}(1-\tilde{\lambda})^2}{(\tilde{x}^2+1)^2}. \tag{44}$$



Figure 3. Surface elevation for different line charge field strengths for the same parameters as in Fig. 2 and the same values of E_0. This corresponds to λ now ranging from 5.6 to 12.2 nC/cm.

Here $\tilde{\lambda} = \lambda'/\lambda = \tilde{Q}$.

For large $\tilde{x}$ we proceed as before. We have as $x \to \infty$

$$As \sim \frac{A(1+\tilde{\lambda})^2}{\tilde{x}^2}; \quad Af_0 - G \sim -G; \quad Af_1 \sim \frac{2A(1-\bar{\varepsilon})(1-\tilde{\lambda}^2)}{\tilde{x}^3} \tag{45}$$

so, assuming $\tilde{\eta} \propto \tilde{x}^{-\mu}$, $f_1\tilde{\eta}' \ll \tilde{\eta}'' \ll \tilde{\eta}$, we again have a simple asymptotic expression

$$\tilde{\eta} \sim \frac{A(1+\tilde{\lambda})^2}{G\tilde{x}^2} = \frac{\varepsilon_0\varepsilon_1 E_0^2}{g(\rho_2-\rho_1)L}\frac{\varepsilon_2-\varepsilon_1}{\varepsilon_2+\varepsilon_1}\frac{1}{\tilde{x}^2}, \quad \tilde{\xi} \to \infty. \tag{46}$$

Example numerical calculations are shown in figure 3 for different electric field strenghts, calculated in exactly the same way as for the point charge case.

3.2. The role of surface tension

Before we move on to the dynamical case, let us briefly discuss the role of surface tension. The effect is well illustrated by figure 4 where we plot the elevation with a line charge with four different values of the capillary length: once, twice and thrice that of water as well as no surface tension. The surface tension force seeks to smoothen the surface, making the local radius of curvature as large as possible. Near the maximum of the elevation curve, surface tension seeks to pull the surface down, whereas the direction of the surface tension force is opposite in the regions where the curve is concave up. In general, surface tension counteract any tendency of a surface to curve. This is the reason why only small deformations were observed in experiment [4] where surface tension was important, as opposed to the laser experiments of Delville's group [6–8] who are able to decrease surface tension by many orders of magnitude by operating close to a critical point and thereby effectuate large and strongly nonlinear interface deformations.



Figure 4. Surface elevation for different values of surface tension. Together with the zero surface tension case we plot the results of assuming once twice and thrice the capillary length of water, $l_{c,\mathrm{water}} = 2.8\mathrm{mm}$. Parameters are otherwise as in figure 3 with $E_0 = 10^6\mathrm{V/m}$.

4. Dynamical response in the two-dimensional case

The dynamical response of a liquid-liquid interface to a time-varying radiation pressure is of obvious physical interest. There are several papers dealing with this topic, theoretical and experimental, when the laser illumination is fixed in space. In addition to the references given in Section 1, the recent, extensive treatment of Wunenburger *et al.* [24] is a key reference in that context.

A natural extension of the kind of static theory laid out in the previous sections is to consider the case where the exterior source is not fixed in space, but is moving with a constant velocity V in the x direction, parallel to the interface (the xy plane) at a vertical separation L. As mentioned above, such a situation has already been considered by de Gennes [19] for practical, droplet-pushing purposes. As it is easiest to envisage the situation both conceptually and mathematically in the two-dimensional case, we will assume that a charged line, directed in the y direction, is the moving source. That is, we adopt the same physical model as in Section 3. Our purpose is to examine the time-dependent elevation of the interface, for a given value of V. We will for simplicity assume zero viscosity in the liquids, which means that there is no wake formation behind the line moving through medium 1. We assume V is non-relativistic, and that the magnetic field from the moving charge is thus negligible compared to the electric.

In the discussions in this chapter we shall omit the effects of both viscosity and surface tension in order to make the physical picture more transparent and also simplify the mathematics somewhat. Inclusion of both these physical corrections is straightforward using the same analytical techniques as presented herein, however, and could form a useful extension of it.

Before we commence, we make the physically natural *ansatz* that all physical quantities depend on x and t only through the Galilei transformation variable $\xi = x - Vt$. This is the same as assuming that in a coordinate system where the charge is at rest, the surface elevation appears stationary. With this we may replace



Figure 5. The geometry of the small control volume used to derive the equation of motion in the dynamic case.

in the following

$$\frac{\partial}{\partial x} = \frac{\mathrm{d}}{\mathrm{d}\xi}; \quad \frac{\partial}{\partial t} = -V\frac{\mathrm{d}}{\mathrm{d}\xi}. \tag{47}$$

Consider now a tall and thin control volume CV as shown in figure 5, intersecting the interface with a small end area $\mathcal{A}$ whose extension is so small that $\eta(\xi)$ is approximately linear inside CV. We let η mean the elevation in the center of CV. Newton's second law for such a volume, which follows from Reynolds' transport theorem, asserts that the z component of the sum of external forces (here pressure and gravity) equals the change of fluid momentum within CV (e.g., Chapter 3 of [25]):

$$\sum F_z^{\mathrm{ext}} = \oint_{\partial\mathrm{CV}} \rho w \mathbf{v}\cdot \mathrm{d}\mathbf{A} + \frac{\partial}{\partial t}\int_{\mathrm{CV}} \rho w \mathrm{d}\mathcal{V} \tag{48}$$

Here we let the decomposition of the velocity vector be $\mathbf{v} = u\hat{\mathbf{x}} + w\hat{\mathbf{z}}$, $\mathrm{d}\mathbf{A}$ is directed out of the control surface ∂CV, and $\mathrm{d}\mathcal{V}$ denotes volume integration.

The sum of the external forces, including gravity, hydrostatic pressure and the pressure discontinuity at the surface due to electromagnetic forces and surface tension, is easily ascertained to be given by the same expressions as used in the previous sections,

$$\sum F_z^{\mathrm{ext}} = \mathcal{A}(p_{\mathrm{EM}} + p_{\mathrm{s.t.}} - \Delta\rho g\eta) \tag{49}$$

and we need not derive this again. p_{EM} and $p_{\mathrm{s.t.}}$ have the same meaning as in section 3, but with ξ replacing x in p_{EM}.

Treating the right hand side of equation (48) is a little more involved. First, let the heights a^- and a^+ (see figure 5) be large, so that w is zero at the end surfaces (clearly, w must tend to zero far from the interface). To linear order there is no flux across the side surfaces of ∂CV. That disposes of the surface integral. We are left with

$$\sum F_z^{\mathrm{ext}}(\xi) = \mathcal{A}\rho_2\frac{\partial}{\partial t}\int_{-\infty}^{\eta} w(\xi,z)\mathrm{d}z + \mathcal{A}\rho_1\frac{\partial}{\partial t}\int_{\eta}^{\infty} w(\xi,z)\mathrm{d}z. \tag{50}$$

We now require knowledge of how the z-velocity w depends on x and z. Since the surface elevation is assumed small, we are free to make use of the velocity potential ϕ, where $\mathbf{v} = \nabla\phi$. Assuming incompressibility gives the continuity condition $\nabla^2\phi = 0$ which upon further differentiation w.r.t. z implies

$$\Big(\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial z^2}\Big)w = 0. \tag{51}$$

As boundary conditions we clearly must demand that $w(\xi, z = \pm\infty) = 0$. Furthermore the so-called kinematic boundary condition at a surface is

$$w(\xi, z = \eta) = \dot{\eta} + u\frac{\mathrm{d}\eta}{\mathrm{d}x} \approx \dot{\eta}, \tag{52}$$

since the second term in the middle form is of quadratic order in η/L.

According to the standard method of separation of variables we assume $w(\xi, z) = \Xi(\xi)Z(z)$ and conclude that $\Xi'' = -k^2\Xi$ and $Z'' = k^2 Z$ for some real number k. In Fourier form the solution may then be written

$$w(\xi, z) = VL\int_0^\infty \frac{\mathrm{d}k}{2\pi} w(k)\mathrm{e}^{-k|z-\eta|}\mathrm{e}^{\mathrm{i}k\xi} \tag{53}$$

which is seen to solve (51) and fulfil boundary conditions at infinite $|z|$. Of course, the physical value is the real part of this. We next define the complex elevation

$$\eta_c(\xi) = L^2\int_0^\infty \frac{\mathrm{d}k}{2\pi}\eta(k)\mathrm{e}^{\mathrm{i}k\xi} \tag{54}$$

so the kinematic boundary condition (52) gives $w(k) = -\mathrm{i}kL\eta(k)$. With the form (53) the integrals in equation (50) are easy to solve, and inserting the answer into the left hand side of (49) after differentiating using the ansatz (47) we obtain the equation

$$\begin{aligned} &p_{\mathrm{EM}}(\xi, \eta_c, \eta_c') + p_{\mathrm{s.t.}}(\eta_c'') - \Delta\rho g\eta_c \\ &\quad = -V^2L^2(\rho_1 + \rho_2)\int_0^\infty \frac{\mathrm{d}k}{2\pi} k\eta(k)\mathrm{e}^{\mathrm{i}k\xi} = \mathrm{i}V^2(\rho_1 + \rho_2)\eta_c'. \end{aligned} \tag{55}$$

Now we may let $\eta_c = \eta + \mathrm{i}\eta_i$ and write down the real and imaginary parts of equation (55) separately. To simplify the picture somewhat, consider the system when there is no surface tension, $\sigma = 0$. For the parameters used in the previous sections, this hardly changes the results, but makes the physics more transparent and also simplifies the numerical treatment considerably since stiffness is avoided and the order of the differential problem is reduced from 4 to 2. Eliminating η_i from the equations we obtain our governing equation without viscosity or surface tension,

$$\Big(f_1\frac{\mathrm{d}}{\mathrm{d}\xi} + f_0 + \Gamma\Big)\Big(f_1\tilde{\eta}' + f_0\tilde{\eta} + s - \Gamma\tilde{\eta}\Big) = -\Upsilon^2\tilde{\eta}''. \tag{56}$$

In order to have nondimensional parameters not containing σ, we have defined here

$$\Gamma = \frac{G}{A} = \frac{2gL(\rho_2 - \rho_1)}{\varepsilon_0(\varepsilon_2 - \varepsilon_1)E_0^2}; \quad \Upsilon = \frac{2V^2(\rho_2 + \rho_1)}{\varepsilon_0(\varepsilon_2 - \varepsilon_1)E_0^2}. \tag{57}$$

Obviously these parameters are measures of the relative strength of gravitational to electromagnetic forces, and inertial to electromagnetic forces, respectively. Explicitly,

$$\begin{aligned} &(f_1^2 + \Upsilon^2)\tilde{\eta}'' + (f_1f_1' + 2f_1f_0 - 2\Gamma f_1)\tilde{\eta}' \\ &+[f_1f_0' + (f_0 - \Gamma)^2]\tilde{\eta} + f_1s' + (f_0 - \Gamma)s = 0. \end{aligned} \tag{58}$$

where $f_1(\tilde{\xi}), f_0(\tilde{\xi}), s(\tilde{\xi})$ (argument $\tilde{\xi}$ suppressed above) are as defined in (42)-(44) upon $x \to \xi$. We have nondimensionalized as before $\tilde{\xi} = \xi/L$.

4.1. Asymptotics and numerical solution

Repeating our previous exercise of taking the large ξ asymptotics of the different coefficient functions we find that the asymptotic form of $\tilde{\eta}(\xi)$ is unchanged from the static case if we assume the solution to fall off as a power law as $\xi^{-\mu}$ at infinity,

$$\tilde{\eta}(\xi) \sim \frac{s(\xi)}{\Gamma} \sim \frac{\varepsilon_0 \varepsilon_1 E_0^2}{g(\rho_2 - \rho_1)L} \frac{\varepsilon_2 - \varepsilon_1}{\varepsilon_2 + \varepsilon_1} \frac{1}{\tilde{\xi}^2}, \quad \tilde{\xi} \to \infty. \tag{59}$$

The asymptotic form of $\tilde{\eta}'$ is thus $\tilde{\eta}' \sim -2\tilde{\eta}/\tilde{\xi}^3$, which together form a useful set of boundary conditions at large ξ. This condition must clearly hold *in front* of the moving charge, in accordance with our assumption that the liquid surface is at rest before the arrival of the line charge.

However, since our liquid is assumed inviscid, $\tilde{\eta}$ no longer needs to tend to zero at infinity now that we consider a system which is not in mechanical equilibrium. To wit, behind the moving line charge we might expect waves to form since the charge, after setting the surface in motion, moves on and leaves it to oscillate in its wake. When not assuming η to tend to zero, the asymptotic equation from (58) must also include a $\tilde{\eta}''$ term,

$$\Upsilon^2 \tilde{\eta}'' + \Gamma^2 \tilde{\eta} \sim \Gamma \frac{(1 + \tilde{\lambda})^2}{\tilde{x}^2}. \tag{60}$$

We shall not dwell on the particular solution to this equation (which can be found!), but note rather that equation (60) has two homogeneous solution which do not vanish at infinity,

$$\tilde{\eta} = C_1 \cos \frac{\Gamma \xi}{\Upsilon} + C_2 \sin \frac{\Gamma \xi}{\Upsilon} \tag{61}$$

with integration constants C_1 and C_2 which we are not in a position to evaluate in a simple way. This asymptotic form must be valid far *behind* the moving charge where the surface has been disturbed and moves as an undamped wave.

Notice at this point how our theory is valid when $V = 0$ (the static case considered before) and when V is sufficiently large, but *not* when $V/\sqrt{gL}$ is small. The reason is that we have assumed not only that $\tilde{\eta} \ll 1$, but also $\tilde{\eta}' \ll 1$, in order to get rid of the terms $(1 + \tilde{\eta}'^2)^{-1/2}$. However, when V is small, the wavelength of the waves in the wake becomes short,

$$\lambda = \frac{2\pi\Upsilon}{\Gamma} = 2\pi \frac{V^2}{gL} \frac{\rho_2 + \rho_1}{\rho_2 - \rho_1} \tag{62}$$

and the derivative becomes proportional to gLV^{-2}. Note that this wavelength is independent of the electromagnetic properties, and is simply a measure of the relative strength of the forces of inertia and gravity.

In figure 6 we plot the solution for a line charge moving towards the right at different velocities. At large V there are no problems, but already at the two lowest values of V we are in fact pushing the boundaries of linear theory, since $\tilde{\eta}'$ goes as high as 0.5. Equation (58) predicts very high maximum elevation for small velocities, but this is wrong and happens because the compensating factor, such as the square root denominator in equation (36), is not included. The highest peaks may be slightly overestimated in figure 6, therefore.

We observe a number of interesting features. For example, when velocity is small, the peak is in fact higher than the static, mechanical equilibrium value. This is because the rising liquid continues beyond the equilibrium value before the influence of gravity



Figure 6. Surface elevation in the absence of surface tension and viscosity for a charge moving at velocity V towards the right [particle position $(x, z) = (Vt, L)$]. We let $\rho_2 g = 9790\text{N/m}^3$ and $\rho_1 \approx 0$ as in the case of a water/air interface. The dotted line shows the static mechanical equilibrium situation (also for $\sigma = 0$).

finally makes it turn and fall back again. On the other hand, when the line charge moves fast, the fluid only reaches its maximum velocity some time after the charge has moved on. We also see that the *amplitude* of the harmonic oscillations is a non-trivial function of V. When the movement is very slow, oscillations are very small, since the charge, after lifting the surface, stays around to set it gently back down again. This is what we see in figure 6 for the two slowest velocities. When V is *very* high, likewise, oscillations must, in addition to having long wavelength, be of small amplitude, since the surface hardly has time to feel the presence of the charge before it is gone again. Somewhere in between these extremes is found the velocity which gives the maximum oscillation amplitude. Finally, we see that for small velocities, the first peak appears *in front* of the line charge, as is the case for $V = 0.4\sqrt{gL}$ in figure 6. For even smaller velocities than this, the surface is lifted up, then drops again due to gravity, whereupon it is lifted again to a second time, since the field from the charge is still present and strongly felt. The beginnings of a second peak are observed in the $0.4\sqrt{gL}$ graph (to fully study this phenomenon, nonlinear theory must be invoked as previously discussed). All in all, our simple set-up treated with linear theory has yielded surprisingly rich physics.

In the previous we have omitted the effects of viscosity, although it is obvious what the effect of its inclusion would be. We have seen that far behind the moving charge, the governing equation takes the form of an undamped harmonic oscillator (or wave) equation. A viscosity term, being proportional to $\dot{\eta}$ would include a damping in this equation, making sure the harmonic waves be damped exponentially behind the moving charge, admitting overdamped and underdamped solutions depending on the relative value of viscosity and wave number Γ/Υ. Studying this effect is

straightforward within the above framework [a friction force is simply added to the right hand side of equation (49)]. Along with the effects of surface tension it serves as a useful extension problem for pedagogical purposes.

5. Conclusions

We have considered the basic electrohydrodynamic case of a point charge and a line charge above a fluid-fluid interface. The electric field from the charge acts on the dielectric interface, causing it to rise above the equilibrium level. In the static case the shape of the fluid-fluid interface is determined by the relative strength of three forces acting on it: the electromagnetic lifting force, gravity and surface tension.

For small elevations the deformation can be described by a single ordinary differential equation which is readily solved numerically. We derive and solve this equation for the case of a point charge and a line charge. When surface tension is small the maximum height of the surface is determined by a dimensionless number which is the relative weight of the electric lifting force vs. gravity. The effect of surface tension is to counteract the tendency of the other forces to induce surface curvature, which we illustrate in figure 4.

Finally we derived the dynamical equation of motion for a surface subject to a line charge moving at a constant velocity. Altough apparently just a small generalization of the static case, the system is surprisingly rich in physics. As the moving line charge goes past, the liquid surfaces is elevated from its unperturbed level and is left to oscillate around an equilibrium level as the charge moves away [we assume inviscid fluid, so the oscillations are undampled]. The details of the time dependent movement of the fluid surface, however, depend nontrivially on the speed at which the charge moves, compared to a reference velocity $\sqrt{gL}$ [L being the smallest distance from charge to undisturbed surface]. For high velocities the surface hardly has time to react to the presence of the charge, and the oscillations have long wavelength and small amplitude. For low velocities the oscillation wavelength is short, and the maximum elevation can be considerably higher than that of static equilibrium. The amplitude of oscillations behind the charge are small also in this extreme, however, since the charge has time to set the surface gently back behind it. In between these extremes is found the velocity giving the highest amplitude of oscillations behind the moving charge.

References

[1] Fan X and White I M 2011 *Nature Photonics* **5** 591.
[2] Monat C, Domachuk P and Eggleton B J 2007 *Nature Photonics* **1** 106 .
[3] Psaltis D, Quake S R and Yang C 2006 *Nature* **442** 381.
[4] Ashkin A and Dziedzic J M 1973 *Phys. Rev. Lett.* **30** 139.
[5] Zhang J Z and Chang R K 1988 *Opt. Lett.* **13** 916.
[6] Casner A and Delville J-P 2004 *EPL* **65** 337.
[7] Delville J-P, de Saint Vincent M R, Schroll R D, Chraïbi H, Issenmann B, Wunenburger R, Lasseux D, Zhang W W and Brasselet E 2009 *J. Opt. A: Pure Appl. Opt.* **11** 034015.
[8] Wunenburger R, Issenmann B, Brasselet E, Loussert C, Hourtane V and Delville J-P 2011 *J. Fluid Mech.* **666** 273.
[9] Hallanger A, Brevik I, Haaland S and Sollie R 2005 *Phys. Rev. E* **71** 056601.
[10] Delville J-P, Casner A, Wunenburger R and Brevik I 2006 *Trends in Electro-Optic Research* (New York: Nova Science), p 1.
[11] Taylor G I 1969 *Proc. R. Soc. London Ser. A* **313** 453.
[12] Raco R J 1968 *Science* **160** 311.
[13] Saville D A 1970 *Phys. Fluids* **13** 2987.

[14] Sankaran S and Saville D A 1992 *Phys. Fluids A* **5** 1081.
[15] Burcham C L and Saville D A 2000 *J. Fluid Mech.* **405** 37.
[16] Pelekasis N A, Economou K and Tsamopoulos J A 2001 *Phys. Fluids* **13** 3564.
[17] Terasawa H, Mori Y H and Komotor K 1983 *Chem. Eng. Sci.* **38** 567.
[18] Dong J, de Almeida V F and Tsouris C 2011 *J. Coll. Interf. Sci.* **242** 327.
[19] de Gennes P G 2005 *Compt. Rendus Physique Paris* **6** 1149.
[20] Brevik I 1979 *Phys. Rep.* **52** 133
[21] Landau L D, Lifshitz E M and Pitaevskii L P 1984 *Electrodynamics of Continuous Media* 2nd ed. (Oxford: Pergamon Press), §7
[22] Landau L D, Lifshitz E M 1987 *Fluid Mechanics* 2nd ed. (Oxford: Butterworth-Heinemann), §61
[23] Wehausen J V and Laitone E V 1960 *Surface Waves* (*Encyclopedia of Physics* vol IX) (Berlin: Springer).
[24] Wunenburger R, Casner A and Delville J-P 2006 *Phys. Rev. E* **73** 036315.
[25] White F M 2003 *Fluid Mechanics* 5th ed. (New York: McGraw-Hill).